



Air conditioners

# Heating & Cooling

*Siesta*

Wall mounted unit

- » SEER/SCOP: up to **A<sup>+</sup>**
- » Easy control at your fingertips
- » Turbo mode
- » Anti-corrosion treated outdoor unit
- » Wide range, from 25 to 60 class



[www.daikin.eu](http://www.daikin.eu)



ATXV-AB



Inverter



Fan only



Comfortable sleeping mode



Vertical auto swing



Auto fan speed



Fan speed steps



Dry programme



24 hour timer



Infrared remote control



Auto-restart

# Heating & Cooling

Indoor unit			ATXV25AB	ATXV35AB	ATXV50AB	ATXV60AB		
Cooling capacity	Nom.	kW	2.65	3.4	5.2	6.25		
Heating capacity	Nom.	kW	2.8	3.84	5.65	6.75		
Seasonal efficiency (according to EN14825)	Cooling	Energy label		A+		A		
		Pdesign	kW	2.65	3.40	5.20	6.25	
		SEER		5.60		5.10		
	Heating (Average climate)	Annual energy consumption		166	213	325	429	
		Energy label		A				
		Pdesign	kW	2.80	3.20	4.50	5.80	
	SCOP		3.80	3.92	3.80			
	Annual energy consumption	kWh	1,032		1,143	1,658	2,137	
Dimensions	Unit	HeightxWidthxDepth	mm		275x845x180	298x940x200	315x1,007x219	
Weight	Unit		kg		9	12	14	
Fan-Air flow rate	Cooling	High/Nom./Low/Silent operation	m <sup>3</sup> /min		10/8.3/6.7/5	9.7/8.3/6.7/5	14.2/13/10.8/9.2	16.7/13.3/11.7/9.2
Sound power level	Cooling	/	dBA		50	51	63	58
Sound pressure level	Cooling	High/Nom./Low/Silent operation	dBA		41/39/34/28	42/40/35/30	48/43/40/35	51/47/42/39
Piping connections	Liquid	OD	mm		6.35			
	Gas	OD	mm		9.52	12.7	15.9	
	Drain	OD	mm		-			
Power supply	Phase / Frequency / Voltage		Hz / V		1~ / 50 / 220-240			

Outdoor unit			ARXV25AB	ARXV35AB	ARXV50AB	ARXV60AB		
Dimensions	Unit	HeightxWidthxDepth	mm		540x776x320	700x955x396	790x980x427	
Weight	Unit		kg		28	29	45	60
Sound power level	Cooling	/	dBA		63		68	63
Sound pressure level	Cooling	Nom.	dBA		51	53	56	58
Operation range	Cooling	Ambient	Min.~Max.	°CDB		18~43		
	Heating	Ambient	Min.~Max.	°CWB		-10~24		
Refrigerant	Type			R-410A				
	GWP			1,975				
Piping connections	Liquid	OD	mm		6.35			
	Gas	OD	mm		9.52	12.7	15.9	
	Piping length	OU - IU	Max.	m		15	25	
	Level difference	IU - OU	Max.	m		10		
Power supply	Phase / Frequency / Voltage		Hz / V		1~/50/220-240			



Indoor unit ATXV-AB



Infrared remote control



Outdoor unit ARXV-AB

Daikin has a worldwide reputation based on 90 years' experience in the successful manufacture of high quality air conditioning equipment for residential, commercial and industrial use and 56 years as a leader in heat pump technology.



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.

Daikin products are distributed by: