

# Wall mounted unit

ATXN-NB9



*Siesta*



Comfortable sleeping mode



Vertical auto swing



24 hour timer

Siesta wall mounted unit, offering good value for money and ensuring a steady supply of clean air

- › Flat, stylish front panel blends easily within any interior décor and is easier to clean
- › Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room
- › The infrared remote control is user friendly and equipped with a timer function that enables you to programme the unit to start or stop at your desired time.

# ATXN-NB9 + ARXN-NB9





Indoor unit		ATXN	25NB9	35NB9	50NB9	60NB9
Casing	Colour	White				
Dimensions	Unit	288x859x209		310x1,124x237		
Sound power level	Cooling	53	54	55	61	
Sound pressure level	Cooling	41/40/29/21	42/41/30/22	44/40/35/32	46/43/37/33	
Refrigerant	Type	-				
	GWP	-				

Efficiency data		ATXN + ARXN	25NB9 + 25NB9	35NB9 + 35NB9	50NB9 + 50NB9	60NB9 + 60NB9	
Cooling capacity	Nom.	kW	2.560	3.410	5.480	6.230	
Heating capacity	Nom.	kW	2.840	3.580	5.620	6.400	
Power input	Cooling	Nom.	0.693	1.060	1.668	1.931	
	Heating	Nom.	0.700	0.950	1.550	1.680	
Seasonal efficiency (according to EN14825)	Cooling	Energy label	A+				
		Pdesign	kW	2.56	3.41	5.48	6.23
		SEER		5.66	5.86	5.79	5.96
		Annual energy consumption	kWh	159	204	331	366
	Heating (Average climate)	Energy label	A+				
		Pdesign	kW	2.41	2.80	3.37	3.80
		SCOP/A		4.00		4.01	4.06
		Annual energy consumption	kWh	842	981	1,177	1,310
Nominal efficiency	EER		3.69	3.22	3.29	3.23	
	COP		4.06	3.77	3.63	3.81	
	Annual energy consumption	kWh	347	530	833	964	
	Energy label	Cooling/Heating	A/A				

Outdoor unit		ARXN	25NB9	35NB9	50NB9	60NB9
Dimensions	Unit	550x658x289		628x855x328		753x855x328
Sound power level	Cooling	58	60	64	65	
Sound pressure level	Cooling	45	46		51	
Operation range	Cooling	Ambient	10~46		-10~46	
	Heating	Ambient	-15~18			
Refrigerant	Type/Charge/GWP	kg/TCO <sub>2</sub> eq	R-410A/0.74/1.5/2,087.5	R-410A/1.00/2.1/2,087.5	R-410A/1.45/3.0/2,087.5	
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240			

**Daikin Europe N.V.** Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · [www.daikin.eu](http://www.daikin.eu) · BE 0412 120 336 · RPR Oostende (Responsible Editor)



16-038 02/16



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.