

Air conditioners

Cooling

Wall mounted unit

- » **Easy control at your fingertips**
- » **Turbo mode**
- » **Anti-corrosion treated outdoor unit**
- » **Wide range, from 25 to 60 class**



www.daikin.eu



FTV-A



Fan only



Comfortable sleeping mode



Vertical auto swing



Auto fan speed



Fan speed steps



Dry programme



24 hour timer



Infrared remote control

Cooling only

Indoor unit				FTV25A	FTV35A	FTV50A	FTV60A
Cooling capacity	Nom.	kW		2.75	3.55	5.2	6.45
Nominal efficiency (cooling at 35°/27° nominal load, heating at 7°/20° nominal load)	EER			3.48	3.41	2.91	3.09
Annual energy consumption		kWh		395	520	895	1,045
Energy label	Cooling			A		C	B
Dimensions	Unit	HeightxWidthxDepth	mm	265x790x174	275x845x180	298x940x200	315x1,007x219
Weight	Unit	kg		9	10	13	15
Fan-Air flow rate	Cooling	High/Nom./Low/Silent operation	m ³ /min	8.3/6.7/5.5/4.7	10.5/8.8/7.5/6	14.2/13/10.8/9.2	16.7/13.8/12.2/10.5
Sound pressure level	Cooling	High/Nom./Low/Silent operation	dB(A)	40/37/35/32	41/38/35/32	47/44/41/37	49/45/41/37
Piping connections	Liquid	OD	mm	6.35			
	Gas	OD	mm	9.52	12.7		15.9
Power supply	Phase / Frequency / Voltage		Hz / V	1~/50/220-240			

Outdoor unit				RV25A	RV35A	RV50A	RV60A
Dimensions	Unit	HeightxWidthxDepth	mm	540x848x320			700x955x396
Weight	Unit	kg		29	33	45	52
Compressor	Type		Rotary				
Sound pressure level	Cooling	Nom.	dB(A)	50	52	56	
Operation range	Cooling	Ambient	Min.-Max. °CDB	18~43			
Refrigerant	Type		R-22				
Piping connections	Liquid	OD	mm	6.35			
	Gas	OD	mm	9.52	12.7		15.9
	Piping length	OU - IU	Max. m	15	20	25	
	Level difference	IU - OU	Max. m	10			
Power supply	Phase / Frequency / Voltage		Hz / V	1~/50/220-240			



Indoor unit FTV-A



Infrared remote control



Outdoor unit RV-A

Daikin has a worldwide reputation based on 90 years' experience in the successful manufacture of high quality air conditioning equipment for residential, commercial and industrial use and 56 years as a leader in heat pump technology.



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe NV. Daikin Europe NV. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe NV. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe NV.

Daikin products are distributed by: